

Bitwise Operations

CSE 220: Systems Programming

Ethan Blanton & Carl Alphonse

Department of Computer Science and Engineering
University at Buffalo



Planning: Diagrams

After a once-through of the documentation, [start drawing](#).

(See the PA2 Handout video!)

Draw [the ideas](#):

- Data structures
 - Abstract the structure!
 - Arrows represent connections
 - Boxes represent data storage
 - ...
- Program flow
 - Read args → open inputs → ...
 - (This is more interesting if it's non-linear!)

Planning: Pseudocode

After diagrams, **write pseudocode**.

You can write it at a very high level:
“For every cell in the matrix”

Then **put it in your code as comments**.

Augment the comments with code as you develop!

```
// For every cell in the matrix  
//   Compute neighbors
```

Planning: Pseudocode

After diagrams, **write pseudocode**.

You can write it at a very high level:
“For every cell in the matrix”

Then **put it in your code as comments**.

Augment the comments with code as you develop!

```
// For every cell in the matrix
for (int y = 0; y < GRIDY; y++) {
    for (int x = 0; x < GRIDX; x++) {
        // Compute neighbors
    }
}
```

Bitwise Operations

We have seen **arithmetic** and **logical** integer operations.

C also supports **bitwise** operations.

These operations correspond to **circuit elements**.

They are often related to, yet **different from**, logical operations.

The major operations are:

- Bitwise complement
- Bit shifts (left and right)
- Bitwise AND, OR, and XOR

Truth Tables

You should already be familiar with [truth tables](#).

Every bitwise operation (except shift) is defined by a truth table.

A truth table represents [one or two input bits](#) and their [output bit](#).

For example, [bitwise OR](#):

x	y	Result
0	0	0
1	0	1
0	1	1
1	1	1

Bitwise Operations

OR ($\vee$):

x	y	Result
0	0	0
1	0	1
0	1	1
1	1	1

XOR ($\oplus$):

x	y	Result
0	0	0
1	0	1
0	1	1
1	1	0

AND ($\wedge$):

x	y	Result
0	0	0
1	0	0
0	1	0
1	1	1

NOT ($\neg$):

x	Result
0	1
1	0

Bit Operations on Words

Each of these bit operations can be applied to any **integer type**.

Each **bit position** will have the operation applied individually.

E.g., the application of XOR to an n-bit word is:

$$\forall_{i=0}^{n-1} \text{Result}_i = x_i \oplus y_i$$

Each operation applies to a **single bit**, so no carries are needed.

Lecture Question

Time for a review question!

Operators

The C bitwise operators divide into **unary** and **binary** operators:

Unary:

- $\sim x$: Bitwise complement of x ($0 \rightarrow 1, 1 \rightarrow 0$)

Binary:

- $x \mid y$: Bitwise OR of x and y
- $x \& y$: Bitwise AND of x and y
- $x \wedge y$: Bitwise XOR of x and y
- $x \ll y$: Left shift x by y bits
- $x \gg y$: Right shift x by y bits

Bit Shifting

Bit shifts are slightly more complicated.

C can shift bits left or right.

- Left shift (<<): bits move toward larger bit values
- Right shift (>>): bits move toward smaller bit values

For left shift, zeroes are shifted in on the right.

Examples:

0111 left shift 1 bit → 1110

0010 left shift 2 bits → 1000

Right Shifts

Right shifts are somewhat trickier.

In particular, they may obey sign extension.

If the shifted integer is unsigned, zeroes are shifted in on the left:

0110 right shift 1 bit → 0011

1010 right shift 2 bits → 0010

If the shifted integer is signed, the sign bit may affect the shift.

- If it is zero, shifts behave as unsigned
- If it is one, it might shift in ones

If [the shifted value] is a signed type and a negative value, the resulting value is implementation-defined. — ISO C99

Bit versus Logical Operators

Do not confuse the bit and logical operators!

Some of them work correctly for integers; e.g., `|`.

Some decidedly do not, e.g., `&`:

`1 & 2` → logical false!

Not (`~`) and and (`&`) are particularly pernicious because they often work.

Masking

Many bitwise operations are used to work on a **portion** of a word.

This typically requires **masking** either:

- The bits to be modified
- The bits to be ignored

Masking uses `&` and sometimes `~`.

For example, to get the **lowest 8 bits** of an integer:

```
eightbits = x & 0xff;
```

(You might remember this from `dumpmem()`.)

Bit Twiddling

Setting and unsetting **individual bits** typically uses masking.

Assume we want to **set bit zero**:

```
#define LOWBIT 0x1
```

```
x = x | LOWBIT;
```

Later, we want to **unset bit zero**:

```
x = x & ~LOWBIT;
```

In this case, $\sim\text{LOWBIT}$ is a mask for **all bits except 0**.

Twiddling with XOR

If you always want to **complement** a bit, you can use XOR.

This comes from the truth table; assume y is a constant 1:

x	y	Result
0	0	0
1	0	1
0	1	1
1	1	0

```
x = x ^ LOWBIT;
```


Shifting and Powers of 2

Note that **bit shifting left is multiplying by powers of 2!**

A one-bit left shift is multiplying by 2:

0010 $\rightarrow$ 2

0100 $\rightarrow$ 4

0011 $\rightarrow$ 3

0110 $\rightarrow$ 6

Successive bit shifts continue to multiply by 2.

1 ($= 2^0$)

1 $\ll k$ ($= 2^k$)

Lecture Question

Ask a lecture question!

Forcing Endianness

```
int htonl(int input) {  
    int output;  
    char *outb = (char *)&output;  
    for (int b = 0; b < sizeof(int); b++) {  
        int shift = (sizeof(int) - b - 1) * 8;  
        outb[b] = (input >> shift) & 0xff;  
    }  
    return output;  
}
```

htonl in Action

```
int x = 0x01020304;  
int y = htonl(x);
```

```
dump_mem(&x, sizeof(x));  
dump_mem(&y, sizeof(y));
```

```
04 03 02 01  
01 02 03 04
```

Summary

- C can manipulate **individual bits** in memory.
- Bit operations can be **subtle and tricky!**
- **Signedness** matters.
- Bit manipulations can **force endianness** or other representations.

References I

Required Readings

- [2] Brian W. Kernighan and Dennis M. Ritchie. *The C Programming Language*. Second Edition. Chapter 2: 2.9; Appendix A: A7.4.6, A7.8, A7.11–A7.13. Prentice Hall, 1988.
- [3] Ian Weinand. *Computer Science from the Bottom Up*. Chapter 2, part 1: 1.1.4, 1.1.5, 1.3. URL: <https://www.bottomupcs.com/index.html>.

Optional Readings

- [1] Randal E. Bryant and David R. O'Hallaron. *Computer Science: A Programmer's Perspective*. Third Edition. Chapter 2: 2.1.6–2.1.9. Pearson, 2016.

License

Copyright 2019–2025 Ethan Blanton, All Rights Reserved.

Copyright 2024 Eric Mikida, All Rights Reserved.

Copyright 2022–2025 Carl Alphonse, All Rights Reserved.

Copyright 2019 Karthik Dantu, All Rights Reserved.

Reproduction of this material without written consent of the author is prohibited.

To retrieve a copy of this material, or related materials, see <https://www.cse.buffalo.edu/~eblanton/>.