

Design a Dynamic Programming Algorithm

- Consider the instance: $i, W', (w_1, w_2, \dots, w_i)$;
- $opt[i, W']$: the optimum value of the instance

Q: The value of the optimum solution that **does not contain** i ?

A: $opt[i - 1, W']$

Q: The value of the optimum solution that **contains** i ?

A: $opt[i - 1, W' - w_i] + w_i$

Dynamic Programming

- Consider the instance: $i, W', (w_1, w_2, \dots, w_i)$;
- $opt[i, W']$: the optimum value of the instance

$$opt[i, W'] = \begin{cases} & i = 0 \\ & i > 0, w_i > W' \\ & i > 0, w_i \leq W' \end{cases}$$

Dynamic Programming

- Consider the instance: $i, W', (w_1, w_2, \dots, w_i)$;
- $opt[i, W']$: the optimum value of the instance

$$opt[i, W'] = \begin{cases} 0 & i = 0 \\ & i > 0, w_i > W' \\ & i > 0, w_i \leq W' \end{cases}$$

Dynamic Programming

- Consider the instance: $i, W', (w_1, w_2, \dots, w_i)$;
- $opt[i, W']$: the optimum value of the instance

$$opt[i, W'] = \begin{cases} 0 & i = 0 \\ opt[i - 1, W'] & i > 0, w_i > W' \\ & i > 0, w_i \leq W' \end{cases}$$

Dynamic Programming

- Consider the instance: $i, W', (w_1, w_2, \dots, w_i)$;
- $opt[i, W']$: the optimum value of the instance

$$opt[i, W'] = \begin{cases} 0 & i = 0 \\ opt[i - 1, W'] & i > 0, w_i > W' \\ \max \left\{ \begin{array}{c} opt[i - 1, W'] \\ opt[i - 1, W' - w_i] + w_i \end{array} \right\} & i > 0, w_i \leq W' \end{cases}$$

Dynamic Programming

```
1: for  $W' \leftarrow 0$  to  $W$  do
2:    $opt[0, W'] \leftarrow 0$ 
3: for  $i \leftarrow 1$  to  $n$  do
4:   for  $W' \leftarrow 0$  to  $W$  do
5:      $opt[i, W'] \leftarrow opt[i - 1, W']$ 
6:     if  $w_i \leq W'$  and  $opt[i - 1, W' - w_i] + w_i \geq opt[i, W']$  then
7:        $opt[i, W'] \leftarrow opt[i - 1, W' - w_i] + w_i$ 
8: return  $opt[n, W]$ 
```

Recover the Optimum Set

```
1: for  $W' \leftarrow 0$  to  $W$  do
2:    $opt[0, W'] \leftarrow 0$ 
3: for  $i \leftarrow 1$  to  $n$  do
4:   for  $W' \leftarrow 0$  to  $W$  do
5:      $opt[i, W'] \leftarrow opt[i - 1, W']$ 
6:      $b[i, W'] \leftarrow N$ 
7:     if  $w_i \leq W'$  and  $opt[i - 1, W' - w_i] + w_i \geq opt[i, W']$ 
then
8:        $opt[i, W'] \leftarrow opt[i - 1, W' - w_i] + w_i$ 
9:        $b[i, W'] \leftarrow Y$ 
10: return  $opt[n, W]$ 
```

Recover the Optimum Set

```
1:  $i \leftarrow n, W' \leftarrow W, S \leftarrow \emptyset$ 
2: while  $i > 0$  do
3:   if  $b[i, W'] = Y$  then
4:      $W' \leftarrow W' - w_i$ 
5:      $S \leftarrow S \cup \{i\}$ 
6:    $i \leftarrow i - 1$ 
7: return  $S$ 
```

Running Time of Algorithm

```
1: for  $W' \leftarrow 0$  to  $W$  do
2:    $opt[0, W'] \leftarrow 0$ 
3: for  $i \leftarrow 1$  to  $n$  do
4:   for  $W' \leftarrow 0$  to  $W$  do
5:      $opt[i, W'] \leftarrow opt[i - 1, W']$ 
6:     if  $w_i \leq W'$  and  $opt[i - 1, W' - w_i] + w_i \geq opt[i, W']$  then
7:        $opt[i, W'] \leftarrow opt[i - 1, W' - w_i] + w_i$ 
8: return  $opt[n, W]$ 
```

Running Time of Algorithm

```
1: for  $W' \leftarrow 0$  to  $W$  do
2:    $opt[0, W'] \leftarrow 0$ 
3: for  $i \leftarrow 1$  to  $n$  do
4:   for  $W' \leftarrow 0$  to  $W$  do
5:      $opt[i, W'] \leftarrow opt[i - 1, W']$ 
6:     if  $w_i \leq W'$  and  $opt[i - 1, W' - w_i] + w_i \geq opt[i, W']$  then
7:        $opt[i, W'] \leftarrow opt[i - 1, W' - w_i] + w_i$ 
8: return  $opt[n, W]$ 
```

- Running time is $O(nW)$

Running Time of Algorithm

```
1: for  $W' \leftarrow 0$  to  $W$  do
2:    $opt[0, W'] \leftarrow 0$ 
3: for  $i \leftarrow 1$  to  $n$  do
4:   for  $W' \leftarrow 0$  to  $W$  do
5:      $opt[i, W'] \leftarrow opt[i - 1, W']$ 
6:     if  $w_i \leq W'$  and  $opt[i - 1, W' - w_i] + w_i \geq opt[i, W']$  then
7:        $opt[i, W'] \leftarrow opt[i - 1, W' - w_i] + w_i$ 
8: return  $opt[n, W]$ 
```

- Running time is $O(nW)$
- Running time is **pseudo-polynomial** because it depends on value of the input integers.

Running Time of Algorithm

```
1: for  $W' \leftarrow 0$  to  $W$  do
2:    $opt[0, W'] \leftarrow 0$ 
3: for  $i \leftarrow 1$  to  $n$  do
4:   for  $W' \leftarrow 0$  to  $W$  do
5:      $opt[i, W'] \leftarrow opt[i - 1, W']$ 
6:     if  $w_i \leq W'$  and  $opt[i - 1, W' - w_i] + w_i \geq opt[i, W']$  then
7:        $opt[i, W'] \leftarrow opt[i - 1, W' - w_i] + w_i$ 
8: return  $opt[n, W]$ 
```

- Running time is $O(nW)$
- Running time is **pseudo-polynomial** because it depends on value of the input integers.
- Game's running time:
<https://courses.csail.mit.edu/6.5440/fall23/>

Avoiding Unnecessary Computation and Memory Using Memoized Algorithm and Hash Map

compute-opt(i, W')

```
1: if  $opt[i, W'] \neq \perp$  then return  $opt[i, W']$ 
2: if  $i = 0$  then  $r \leftarrow 0$ 
3: else
4:    $r \leftarrow \text{compute-opt}(i - 1, W')$ 
5:   if  $w_i \leq W'$  then
6:      $r' \leftarrow \text{compute-opt}(i - 1, W' - w_i) + w_i$ 
7:     if  $r' > r$  then  $r \leftarrow r'$ 
8:    $opt[i, W'] \leftarrow r$ 
9: return  $r$ 
```

- Use hash map for opt

Outline

- 1 Weighted Interval Scheduling
- 2 Subset Sum Problem
- 3 Knapsack Problem
- 4 Longest Common Subsequence
 - Longest Common Subsequence in Linear Space
- 5 Shortest Paths in Directed Acyclic Graphs
- 6 Matrix Chain Multiplication
- 7 Optimum Binary Search Tree
- 8 Summary